


LED Canopy Light



PGCS-60W-277-CXX

Driver Info

Type:	Constant Current
100-277Vac:	Yes
277-480Vav:	Not
Input Watts:	60W
Efficiency:	88%

LED Info

Watts:	60W
Color Temp:	5000K
Color Accuracy:	70CRI
L70 Lifespan:	50000
Lumens:	7200
Efficacy:	120LPW

Suitable for wet location and operation in ambient not exceeding 40 °C(104 F)
 Products are not intended for use in environments containing airborne corrosive
 airborne corrosive agents such as chemical.

Color: White
 Weight: 9.6lbs(4.3Kg)



Technical Specifications

FEATURES

- Description: 60W LED Parking Garage Canopy
- Universal 100-277V
- Mercury Free: no UV
- Heavy-duty cast aluminum housing; rust and corrosion proof; polyester powder coating
- 4KV surge protector inside of power supply
- IES/LM79/LM80 data available
- 5 Year Limited Warranty
- Mounting: Wall mounting
- Application: yard, dock, backyard, barns, farms, alleyways, roadway, parking lots, sidewalk, porch, building wall, etc.

CONSTRUCTION

- Heavy-duty cast aluminum housing; rust and corrosion proof; polyester powder coating
- Diffusor: High light transmittance & Polycarbonate with UV
- LEDs: Top grade LED, high-output, long-life;
- Heat Sink: Aluminium sink attached to the housing directly to reduce LED heats and add to life
- LED Driver: IP65/ Constant current
- Finish: Bronze finish. Environmentally friendly polyester powder coatings.

SENSOR

- Photocell
- Microwave Sensor(with/without controller)
- PIR Sensor



Motion Sensor



Controller

BACKUP BATTERY: Yes/ No/ Optional

SPECIFICATION

General Performance

Input Wattage: **60W**, Lumens: **7200**, Efficacy: **120LPW**, Input Voltage: **100-277V/50-60HZ**, CRI: **>70**, CCT: **5000K**, Power Factor: **≥0.9**, THD: **≤20%**, Driver Type: **Constant Current / Class 1**, Surge Protector: **NO**, Luminaire Life: **50000hrs**;

Physical

Dimension: **10"x10"x3.13"(254x254x79.5mm)**, Weight: **9.6 lbs(4.3Kg)**;

Operation Condition

Operating Temperature: **-4 F ~+104 F (-20 C -40 C)**, Humidity: **≤95%**;


Certificate

Certification: **ETL/cETL,DLC4.2**, Environment: **Suitable for Wet Location**, Material: **RoHS compliant**.

Order Information

PGCS	—	Wattage	—	Voltage	—	CCT
PGCS	—	60W	—	277V: 100-277Vac	—	30K: 3000K 40K: 4000K 50K: 5000K
PGCS	—	60W	—	277V	—	


Photometrics




LED Parking Garage

Packaging


6pcs/CTN G.W.:4.3 kg Dimension: 22.2"L x 11.3"W x 15"H (565mmx288mmx382mm)



Container Loading QTY



Size	Corton QTY	Product QTY	Volumn	G.W.
20'gq	480 ctn	2880 pcs	32.24m ³	12384 kg



Size	Corton QTY	Product QTY	Volumn	G.W.
40'gp	960 ctn	5760 pcs	64.48m ³	24768 kg